
WHITE PAPER



SECURING THE FUTURE: DEFENDING MACHINE LEARNING SYSTEMS AGAINST ADVERSARIAL THREATS

Abstract

Machine Learning (ML) and Artificial Intelligence (AI) have rapidly become core enablers of automation, decision intelligence, cybersecurity analytics, fraud prevention, and enterprise-scale digital transformation.

This whitepaper provides a comprehensive, lifecycle-aligned framework for securing ML systems, synthesizing insights from leading global standards such as NIST's Adversarial ML Taxonomy 1, the MITRE ATLAS adversarial threat matrix, and governance guidelines from ISO/IEC 42001 3. It examines the evolving adversarial landscape, identifies attack surfaces across the ML pipeline—from data ingestion and training to deployment and runtime—and articulates the business, operational, and regulatory implications of ML compromise

Infosys
Navigate your next

Executive Summary

Artificial Intelligence (AI) and Machine Learning (ML) have transitioned from experimental technologies to core engines of business value and national competitiveness. Today, ML models drive critical processes such as fraud detection, identity verification, medical diagnostics, cybersecurity analytics, supply-chain optimization, automated decision support, and GenAI-enabled productivity. As organizations expand automation and rely on ML-based decisions, the confidentiality, integrity, and reliability of these models have become mission-critical risks.

However, the rapid rise of AI has also created a high-value target surface for sophisticated adversaries. Unlike traditional software which behaves, ML systems learn patterns from data and can be manipulated through subtle, difficult-to-detect perturbations. This introduces a class of vulnerabilities known as adversarial ML threats, enabling attackers to influence how models behave, degrade accuracy, or even hijack decision-making.

Modern threat actors, including state-sponsored groups, cybercriminals, and commercial competitors are actively exploiting ML weaknesses. Techniques such as adversarial evasion, data poisoning, model extraction, membership inference, and GenAI prompt injection allow adversaries to mislead or compromise ML systems without needing to breach traditional IT controls. These attacks often bypass existing firewalls, SIEM alerts, and endpoint defenses, making ML a preferred path for stealthy influence and financial gain.

The Evolving Threat Landscape

Machine Learning (ML) is rapidly becoming the decision engine of modern enterprises, but its accelerated adoption has simultaneously expanded the opportunities available to attackers. The threat landscape surrounding AI/ML has evolved dramatically over the last five years, driven by three major forces: increasing model complexity, widespread democratization of AI tools, and the rising financial and strategic value of ML-driven systems. As a result, adversaries are no longer targeting infrastructure alone—they are now targeting the models themselves, the data that trains them, and the pipelines that deploy them.

This section explains the key drivers shaping today's adversarial landscape and why traditional cybersecurity strategies are insufficient to protect ML systems.

A New Category of Cyber Risk

Unlike traditional software, ML systems learn from data rather than relying on handcrafted logic. This makes them uniquely susceptible to data-centric manipulation, where small, benign changes can dramatically alter system behavior. Attackers exploit these characteristics through:

Adversarial examples that cause misclassification without being perceptible to humans	**Poisoned datasets** that embed backdoors or bias into models during training	**Extraction techniques** that allow attackers to clone models by querying APIs	**Inference attacks** that allow recovery of sensitive training data	**Prompt or context injections** especially in GenAI systems—that alter model behavior

The result is an attack surface that is both broader and more subtle than legacy systems.



External Document © 2026 Infosys Limited

Rise of Sophisticated Adversaries Targeting AI

Threat actors now see ML systems as high-leverage opportunities. Three categories of adversaries dominate this landscape:

1. Cybercriminals

Organized groups exploit adversarial ML to:

- Bypass fraud detection.
- Evade malware classifiers.
- Manipulate credit risk models.
- Automate large-scale attacks using GenAI.

These groups increasingly use open-source adversarial ML frameworks, reducing the skill barrier for exploitation.

2. Nation-State Actors

State-backed entities target ML models to:

- Influence of public-sector decision systems
- Compromise biometric authentication.
- Stealthily degrade critical infrastructure ML
- Steal proprietary models for economic advantage.

These actors have the motivation and resources to bypass conventional detection.

3. Competitors & Corporate Espionage

Unethical commercial competitors exploit:

- Model extraction to steal IP.
- Membership inference to retrieve sensitive business data.
- Strategic poisoning to diminish model performance over time.

This represents a new dimension of digital economic warfare.

Increased Dependency on Third-Party & Pretrained Models

Modern ML development relies heavily on:

Open-source models (Hugging Face, GitHub)	Foundation models from cloud providers	Third-party datasets	Community contributed architectures

While this accelerates innovation, it introduces **AI supply chain risk** one compromised dataset or model can propagate vulnerabilities across thousands of organizations.

This mirrors the evolution of software supply chain risks seen with Solorigate (Solorigate (also known as SUNBURST) is the name given by Microsoft to a highly sophisticated 2020 supply chain cyberattack) but amplified through ML's sensitivity to training data and hidden model behavior.

The GenAI Explosion Has Multiplied the Attack Surface

GenAI systems like large language models (LLMs), code assistants, chatbots, and RAG-based enterprise copilots have introduced entirely new attack vectors:


Prompt injection: Manipulating model behavior through crafted text	**Indirect prompt injection:** Attacking via emails, documents, or webpages the model consumes	**Jailbreaks:** Bypassing safety constraints
Training data poisoning: Contaminating publicly scraped data	**Hallucination exploitation:** Inducing wrong outputs to trigger unintended actions	**Agent manipulation:** Influencing autonomous AI agents that can execute tasks

Because GenAI models interact dynamically with users, tools, APIs, and external content, attackers now have an interactive pathway to influence enterprise AI systems.

External Document © 2026 Infosys Limited

Economic and Operational Stakes Are Increasing

Organizations are using ML in high-value processes such as:



A compromised model can cause:

- Financial losses (revenue leakage, fraud evasion, SLA violations)
- Safety hazards (misdiagnosis, operational failures in OT/IoT)
- Reputational damage (bias amplification, wrongful decisions)
- Regulatory penalties (privacy breaches, non-compliance with AI governance laws)

This elevates ML security from a technical issue to a board-level business risk.

Expanding Regulatory Pressure & Compliance Expectations

Governments and regulators worldwide are developing AI risk management frameworks, including:

- **EU AI Act** (high-risk AI classification, transparency mandates)
- **ISO/IEC 42001** (AI Management System)
- **NIST AI Risk Management Framework**
- **Singapore Model AI Governance Framework**
- **US Executive Orders on AI Safety and Security**

Enterprises must now show **auditability, explainability, lineage tracking, and robust ML controls**, making adversarial resilience both a regulatory and competitive necessity.



External Document © 2026 Infosys Limited

Why Traditional Security Controls Fall Short

Firewalls, endpoint protection, IAM, and network security cannot detect or mitigate adversarial ML threats because:

- Attacks often look like "normal" API requests.
- Poisoned data appears statistically valid.
- Evasion perturbation can be imperceptible.
- Model theft requires no system compromise—only queries.
- GenAI prompts appear as legitimate user input

ML systems require modelaware, data-aware, and behavior-aware defenses, not just perimeter controls.


The Strategic Imperative for AI Security

The evolving threat landscape demands that enterprises:

- Treat ML systems as **high-value assets**
- Build **ML-specific security architecture**
- Integrate **adversarial defense into MLOps**
- Adopt **Zero Trust for AI models and data pipelines**
- Maintain **continuous monitoring for drift and anomalous behavior**
- Conduct **ML red teaming & stress testing**

Organizations that adapt early will gain resilience, regulatory readiness, and competitive advantage. Those that delay face asymmetric risk that compound over time.

Figure 1. ML Attack Surface Risk Levels



Prioritize controls data at ingress and inference boundaries, where risk concentrates.

External Document © 2026 Infosys Limited

Adversarial Threats to ML

Machine Learning introduces a fundamentally different security paradigm: instead of exploiting software vulnerabilities, attackers exploit mathematical properties of models, statistical weaknesses in data, and blind spots in decision boundaries. The result is a growing ecosystem of adversarial ML threats that can silently compromise integrity, confidentiality, and availability without breaching any traditional IT control.

This section provides a detailed overview of the five dominant adversarial threats facing modern AI systems, each backed by real-world applicability and increasing evidence of malicious activity.

Evasion Attacks

Evasion attacks occur when an adversary crafts input specifically designed to fool a trained model at inference time, without changing the underlying model or data. These examples are often indistinguishable from legitimate samples to human observers, yet they induce misclassification with high confidence.

How they work

Attackers compute the model's gradient or decision surface and then generate minimal perturbations that shift the input across a classification boundary while keeping it visually or statistically normal.

Typical motivations

- Bypassing fraud or risk detection
- Evading malware or spam classifiers
- Fooling biometric verification
- Misleading computer vision systems in autonomous vehicles
- Triggering false negatives in security monitoring systems

Example

A fraudster modifies 2–3 transaction metadata fields by tiny amounts so the transaction resembles a low-risk customer profile, successfully bypassing the fraud detection model.

Why it matters.

Evasion attacks are:

- Easy to generate using open-source tools.
- Effective against blackbox models (no source of access needed)
- Hard to detect using traditional cybersecurity logs.

They represent one of the most prevalent realworld attack vectors today.

Data Poisoning Attacks

Data poisoning targets the training pipeline rather than the deployed model. Attackers intentionally corrupt training data to introduce biases, embed backdoors, or degrade model performance.

Types of poisoning

1.Label flipping

Changing labels so the model learns incorrect associations.

2.Data injection

Introducing malicious or misleading samples into training datasets.

3.Backdoor insertion


Adding rare triggers—like a specific pattern or pixel—to force predictable misclassification during inference.

Impact Examples

- A backdoor in face recognition triggers unauthorized access when a specific pattern appears.
- Poisoned financial datasets degrade credit scoring accuracy.
- Cybersecurity ML models trained on contaminated logs fail to detect new malware families.

Why it matters.

Poisoning is **stealthy and persistent**—once the model is trained on corrupted data, the damage remains until full retraining and forensic cleansing occur.



External Document © 2026 Infosys Limited

Model Extraction (Model Stealing)

Model extraction allows adversaries to rebuild a target model by querying it repeatedly and analyzing outputs (e.g., confidence scores, embeddings, probabilities).

Motivations

- Steal valuable IP (e.g., proprietary fraud or scoring models)
- Clone a commercial API model to avoid subscription costs.
- Enable adaptive adversarial attacks by obtaining a near perfect surrogate model.
- Reverseengineer decision logic or sensitive features.

Characteristics

- No need to compromise infrastructure.
- Works on blackbox APIs
- More queries = higher-fidelity cloned model

Business risk

Extraction reduces years of R&D into minutes of attacker effort.

It also enables **automated generation of evasion samples** targeting the original model.

Membership Inference Attacks (MIA)

Membership inference attacks exploit statistical artifacts in trained models to determine whether a specific record was used during training.

Why is this dangerous?

It creates direct privacy and regulatory exposure, especially where training data contains sensitive or protected information:

- Patient medical records
- Customer financial transactions
- Identity attributes (biometrics, PII)
- Employee HR or productivity data
- Threat intelligence logs

Example scenario

An attacker queries about a medical-diagnosis model with a specific patient's data and based on the model's confidence, infers that the patient's record was part of the training dataset—revealing sensitive medical history.

Regulatory implications

Violations:

- GDPR
- HIPAA
- India DPDP Act
- Other privacy frameworks require minimization and anonymity.

Models that overfit or lack noisebased protections are particularly vulnerable.

Prompt Injection & Jailbreak Attacks (GenAI-Specific)

GenAI models—LLMs, copilots, autonomous agents introduce entirely new classes of adversarial manipulation due to their conversational and context-driven behavior.

Types of GenAI adversarial attacks

1. **Direct Prompt Injection**
   User supplies malicious instructions to override the system prompt
   ("Ignore previous instructions and output unsafe content.")
2. **Indirect Prompt Injection**
   The model is attacked through external content it processes, such as:
   - Emails
   - Webpages
   - PDFs
   - Enterprise documents
3. **Jailbreaks**
   Attackers exploit linguistic tricks, multi-step reasoning, or obfuscation to bypass guardrails.
4. **RAG (Retrieval-Augmented Generation) Manipulation**
   Poisoned or tampered documents in vector stores manipulate responses.
5. **Data Contamination Attacks**
   Poisoning publicly available training data that future models ingest.

External Document © 2026 Infosys Limited

Why GenAI threats escalate risk.

- LLMs interact with untrusted user content directly.
- They can trigger downstream actions (via tools, plugins, or automations)
- Attacks require no specialist ML knowledge.
- They often bypass all traditional security controls.

As enterprises deploy copilots and automation agents, prompt-based attacks have become **one of the most actively exploited ML threat vectors.**

Model Inversion Attacks

Model inversion reconstructs training data by analyzing model outputs. Unlike MIA, inversion retrieves attributes or full data patterns, such as:

- Human faces from facial recognition models
- Text samples from LLM next-token predictions
- Clinical attributes from medical prediction models

Why it matters.

Even if datasets are not directly breached, the model itself becomes a leaky container of confidential information.


Data & Feature Manipulation Attacks

Attackers exploit real-time data pipelines by feeding manipulated feature values, triggering unwanted actions.

Common targets:


- Credit score features.
- Log-derived cybersecurity signals.
- IoT sensor data
- Transaction metadata
- Behavioral biometrics

Since ML models trust the input distribution, these manipulations can cause **silent, high-impact errors** if not monitored.



External Document © 2026 Infosys Limited

Figure 2. Adversarial Attack Mix (Illustrative)



Attack Surface Anatomy

Machine Learning systems differ fundamentally from traditional applications because their behavior is shaped not only by code but also by **data, learned patterns, training pipelines, model artifacts, and dynamic inference contexts.** This creates a multifaceted attack surface that spans the entire ML lifecycle. Understanding this anatomy is essential for designing resilient AI platforms.

Below is a detailed breakdown of the primary layers and threat entry points that adversaries target.

Data Sources & Ingress Layer

This is the **earliest and most vulnerable point** in the ML lifecycle. ML systems rely on diverse data feeds that may originate from:

- Third-party providers
- Public datasets
- Web scraping
- Sensors and IoT devices
- Business systems (ERP, CRM, SIEM, payment gateways)
- User-generated content
- Log aggregation pipelines.

Common Vulnerabilities

- Poisoning or contamination of raw datasets
- Manipulated transaction metadata or behavioral indicators.
- "Shadow data" entering the pipeline outside governance controls.
- Insecure APIs that supply external or partner data
- Lack of schema validation or integrity checks

Risk Impact

Compromised ingested data cascades through feature engineering and training, embedding **long-lived vulnerabilities** into the model.

External Document © 2026 Infosys Limited

Feature Engineering & Data PreProcessing Layer

This is where raw data is cleaned, normalized, encoded, or transformed into features. It is also a high-risk manipulation point.

Attack Vectors

- Feature manipulation: Altering feature distributions to shift model behavior.
- Pipeline tampering: Inserting malicious code into notebooks or transformation scripts.
- Statistical exploitation: Exploiting assumptions in normalization, imputation, or scaling
- Dependency vulnerabilities: Attacks through compromised Python/R data libraries

Risks Introduced

Even minor changes in feature transformations can:

- Dramatically distorted training
- Produce backdoor triggers.
- Leak sensitive information via engineered features.
- Cause long-term concept drift.

Training Pipeline & Compute Environment

The training environment includes notebooks, orchestrators (Airflow, Kubeflow, Azure ML, SageMaker), GPU clusters, and model training code.

Threats

- **Code injection** in training scripts or configuration files.
- **Supply-chain attacks** on ML libraries (e.g., PyTorch, NumPy, TensorFlow)
- **Compromised GPU/compute nodes** used to introduce covert backdoors.
- **Unauthorized training runs** producing unvetted models.
- **Malicious hyperparameter changes** affect robustness or generalization.

Why is it critical?

Compromise here results in systemic corruption: every model trained downstream inherits the vulnerabilities inserted at this stage.

Model Artifacts & Model Registry Layer

After training, models are stored in registries or artifact repositories.

Registry Risks

- Unauthorized modification or replacement of stored models
- Model signing bypasses allowing injection of tampered artifacts.
- Unauthorized approvals in CI/CD pipelines
- Model version rollback attacks, reverting to weaker versions.

IP Theft Vulnerabilities

Registries held:

- Proprietary models
- Embeddings
- Training metadata
- Feature specifications

These are high-value targets for espionage and competitor exploitation.

Deployment & Serving Infrastructure

Models are deployed as:

- Microservices
- REST/GraphQL APIs
- gRPC services
- Edge devices
- Serverless functions
- Inference clusters (GPU/CPU autoscaling)

Attack Vectors

- **Adversarial evasion** using crafted input samples.
- **Extraction attacks** via repeated querying
- **Flooding/DoS on** inference endpoints
- **Bypassing authentication/authorization**
- **Exfiltration through model responses** (e.g., verbose confidence scores)

Key Weaknesses

- Overly permissive inference APIs
- Lack of throttling, monitoring, ABAC/policy enforcement
- Exposure of model internals via debugging endpoints

External Document © 2026 Infosys Limited

ML Runtime & Inference-Time Context

This layer includes real-time data flows, feature generation at inference, catching, and API orchestration.

Risks

- **Feature drift or distribution attacks**
- **Context manipulation in GenAI systems**
- **Injection attacks in text, image, or multimodal inputs**
- **RAG poisoning** where documents fed into retrieval engines are tampered
- **Payloads embedded inside user-uploaded content** (PDFs, images, code snippets)

Dynamic vulnerability

Runtime is where adversaries most commonly target business logic, exploiting:

- High throughput
- Real-time constraints
- Lack of human oversight
- Blind trust in user-supplied content

Monitoring, Logging & Drift Detection Layer

Monitoring systems observe:

- Input distributions
- Prediction patterns
- Confidence levels
- Latency and system KPIs
- Drift and anomaly signals

Threats

- **Telemetry poisoning** — hiding adversarial activity by manipulating logs
- **Blind spots** due to incomplete drift monitoring
- **Silencing attacks** that disable alerts or distort metrics
- **Evasion attempts that stay within statistical thresholds**
- Monitoring failures allow attacks to persist **undetected for months**

ML Supply Chain & Third-Party Dependency Risks

ML systems rely heavily on:

- Pretrained models.
- Open-source libraries
- Public embeddings
- Community datasets
- Model zoos and weights repositories

Risks

- **Trojanized models downloaded from public sources**
- **Dependency supply-chain attacks**
- **Compromised vector embeddings**
- **Training code with hidden malicious logic**

This expands the attack surface well beyond the organization's perimeter.

Human/Operational Attack Surface

People involved in the ML lifecycle introduce additional risks:


- Data scientists use insecure notebooks.
- Shadow ML projects outside governance
- Weak access controls on experimentation clusters
- Insider threats (accidental or deliberate)
- Misconfigured API keys or exposed credentials

Attackers exploit these gaps to gain footholds that bypass traditional IT protections.



External Document © 2026 Infosys Limited

Summary Diagram



Why This Matters to Executives

- Adversaries exploit non-traditional weak points invisible to classic security tools.
- Vulnerabilities across layers interact, creating compounding systemic risks.
- Model integrity can be compromised without breaching infrastructure.
- AI systems require shared responsibility across data, engineering, cyber, and governance teams.
- Attackers only need to succeed once; defenders must secure the entire lifecycle.

Governance & Risk Management for ML Security

Machine Learning systems introduce a fundamentally different risk profile compared to traditional IT systems. Their behavior depends not just on code but also on dynamic data pipelines, evolving model parameters, opaque internal representations, and continuous real-time interactions with user inputs. As a result, securing ML requires a purpose-built governance and risk management framework that extends beyond standard cybersecurity and IT governance models.

This section outlines the principles, organizational constructs, and operational controls needed to establish a mature, enterprise-aligned governance structure for ML security.

The Need for Dedicated ML Governance

Traditional cybersecurity frameworks—while essential—are insufficient for ML because they overlook model-centric risks such as adversarial manipulation, data poisoning, hallucinationdriven harm, and model extraction. A secure ML environment requires:

- **Model level integrity assurance** (signed, verified, reproducible models)
- **Dataset-level provenance** (lineage tracking, quality controls, versioning)
- **Pipeline trustworthiness** (secure, monitored, reproducible training runs)
- **Inference time protections** (input validation, access control, rate limits)
- **Lifecycle visibility** (drift, bias, performance degradation)

Without governance, ML systems become opaque, brittle, and vulnerable to exploitation.



External Document © 2026 Infosys Limited

Core Governance Principles for ML Security

A robust governance framework must be anchored in five strategic principles:

1. Zero Trust for ML

Every dataset, model artifact, deployment step, and pipeline component must be authenticated, verified, and authorized.

Assumptions of trust—especially for training data, open-source models, or thirdparty tools—must be eliminated.

2. Data & Model Provenance

Provenance provides traceability across:

- Data sources and transformations
- Feature engineering logic
- Model training runs.
- Hyperparameters, seeds, and dependencies
- Deployment configurations

This ensures auditability and accountability.

3. Explainability & Transparency

Executives and auditors need visibility into:

- What data trained the model?
- How features influence predictions
- How the model is performing over time
- How it responds under stress or adversarial pressure

4. Continuous Risk Monitoring

ML systems evolve with data and drift; governance must include:

- Ongoing performance checks
- Drift detection
- Anomaly detection
- Bias analysis
- Integrity validation of live traffic

5. Segregation of Duties (SoD)

- Data scientists **build** models.
- ML engineers **deploy** models.
- Security teams **validate** controls.
- Risk/compliance **approve** high-risk deployments.

This prevents insider risks and unintended model release.

Organizational Governance Structure

A mature governance model requires clearly defined roles and accountability across multiple teams:

AI/ML Governance Board

Comprised of CISO, CIO/CTO, Chief Data Officer, Risk, Compliance, and key business owners.

Responsibilities:

- Approve AI use cases and risk classifications.
- Oversee high-risk model assessments.
- Review incidents, metrics, and compliance reports.

Model Risk Management (MRM) Function

Similar to financial model governance, this team validates:

- Data representativeness
- Model assumptions
- Robustness under adversarial pressure
- Compliance with regulatory requirements

ML Security Engineering Team

Responsible for:

- Secure MLOps pipeline
- Model signing & artifact security.
- Automated scanning and policy enforcement
- Pen-testing and adversarial evaluations

Product & Business Owners

Ensure:

- The model aligns with business objectives.
- Risks to customers and operations are identified early.

Legal, Compliance & Privacy

Define:

- Regulatory obligations
- Data consent boundaries
- Retention & anonymization policies

Together, these teams establish **clear lines of defense.**

External Document © 2026 Infosys Limited

Risk Classification for ML Systems

Not all ML models carry equal risk. Governance must classify models based on business criticality and potential impact.

A typical risk categorization includes:

Tier 1 – High-Risk ML Systems

Examples:

- Fraud detection
- Medical diagnostics
- Identity verification
- Cybersecurity detection systems
- Financial scoring models

Requirements:

Adversarial testing, model card documentation, strict SoD, continuous monitoring.

Tier 2 – Medium-Risk Systems

- Process automation
- Recommendation engines
- Customer support bots

Requirements:

Periodic monitoring, risk review, explainability documentation.

Tier 3 – Low-Risk Systems

- Internal analytics
- Non-decisioning models

Requirements:

Basic documentation and operational hygiene.

Model Policies, Standards, & Controls

A secure ML governance program defines enforceable policies for:

1. Data Governance

- Source validation
- Dataset versioning
- Schema enforcement
- PII controls (anonymization, pseudonymization, minimization)
- Integrity checks (hashing, checksum validation)

2. Secure Development & Training Policies

- Approved training environments
- No internet-connected training nodes
- Code signing for pipelines.
- Controlled GPU access
- Mandatory peer review for training scripts

3. Model Registry & Artifact Control

- Signed models with checksum validation.
- Immutable model registries
- Controlled promotion (dev → staging → prod)
- SBOM (Software Bill of Materials) for models

4. Deployment Standards

- ABAC or RBAC for inference APIs
- mTLS or token-based authentication
- Rate-limiting and throttling.
- Input validation for content and structure.

5. Monitoring & Logging

- Drift analysis
- Bias and fairness monitoring
- Anomaly detection
- Logging for inference access patterns



External Document © 2026 Infosys Limited

Risk Assessment & Threat Modeling for ML Systems

A systematic ML risk assessment must include:

1. Adversarial Threat Modeling (MITRE ATLAS)

Evaluate exposures to:

- Evasion
- Poisoning
- Model theft
- Inference attacks
- Prompt injection (for GenAI)
- Data extraction & inversion

2. Business Impact Analysis

- Revenue or fraud loss potential
- Operational disruption
- Customer harm or bias exposure
- Regulatory impact

3. Architectural Review

- Pipeline attacks surface.
- Data lineage gaps
- Logging blind spots
- Dependency & supply chain vulnerabilities

4. Control Effectiveness

Assess:

- Model robustness
- Input sanitization
- Access control strength
- Monitoring maturity

This ensures risk visibility before deployment.

Compliance, Assurance & Auditability

Governance frameworks must map ML systems to regulatory and assurance requirements such as:

- **ISO/IEC 42001 (AI Management System)**
- **NIST AI RMF**
- **GDPR / DPDP (privacy controls)**
- **Sectoral regulations** (BFSI, healthcare, public sector)
- **Model documentation & explainability obligations.**

Executives must maintain:

- Model cards
- Decision logs
- Lineage reports
- Reproducibility evidence
- Drift & monitoring dashboards.


This ensures models are **audit-ready** and aligned with compliance standards.

Continuous Governance Through the ML Lifecycle

Unlike static applications, ML evolves with data. Governance must shift from periodic reviews to continuous assurance:

- Continuous monitoring & drift alerts
- Automated revalidation when data distributions change
- Scheduled adversarial robustness assessments.
- Quarterly model stress tests
- CI/CD pipelines with mandatory security gates

Governance cannot be a one-time checkpoint; it must be an ongoing operational discipline.



Internal Document © 2026 Infosys Limited

Executive Benefits of Strong ML Governance

A well-implemented governance framework delivers:

1. Reduced operational and financial risk

Prevents fraud, leakage, bias, outages, and unsafe decisions.

2. Regulatory compliance & audit readiness

Avoid penalties and enhance trust.

3. Faster, safer scaling of AI initiatives

Clear policies reduce friction and accelerate deployment.

4. Increased model robustness and reliability

Models degrade gracefully under stress rather than catastrophically.

5. Organizational alignment & accountability

Clear ownership improves efficiency and reduces errors.

Technical Defenses & Patterns

Data Controls

- Schema/quality validation; statistical profiling; canonicalization.
- Immutable storage (WORM) and cryptographic signing for golden data.
- Supplier attestation and model cards for third-party inputs.

Model Hardening

- Adversarial training for key models; certification where feasible.
- Differential privacy and regularization for membership inference resistance.
- Ensembles, randomized smoothing, and feature squeezing.
- Inference-time anomaly/adversarial detectors.

Inference Protections

- Input sanitation/content filters for text, image, audio, and code.
- mTLS/OAuth with ABAC and policy-based access (context, device, geo).
- Rate limiting, burst control, and query similarity analysis.
- Shadow/canarying with automated rollback and kill-switches.

GenAI Guardrails

- Prompt shielding (allow/deny patterns) and output moderation.
- Context isolation in RAG; provenance checks and watermark validation.
- Safety/alignment fine-tuning; periodic red teaming with jailbreak corpora.
- PII/toxicity filters and secure tool-use policies.



External Document © 2026 Infosys Limited

Figure 3. Secure MLOps Reference Architecture





Figure 4. Controls Effectiveness Heatmap





External Document © 2026 Infosys Limited

Operating Model & Metrics

- Org: AI Product Owner, ML Security Eng, Model Risk Officer, Incident Response.
- Runbooks: data recall, model rollback, rapid retraining, kill-switch.
- KPIs/KRIs: detection latency, drift incidents, red-team breach rate, time-to-rollback.
- Assurance: lineage reports, model cards, SBOMs, and board packs.

Incident Response for Adversarial ML

As enterprises increasingly rely on ML models for mission critical decisionmaking, adversarial attacks targeting these systems demand a specialized, model-aware Incident Response (IR) capability. Conventional IR processes designed for malware, network breaches, or endpoint compromise are insufficient because adversarial ML incidents involve subtle data manipulation, model degradation, context pollution, or exploit patterns invisible to traditional security tools.

This section provides a comprehensive, lifecycle aligned IR framework tailored for ML and GenAI environments, enabling organizations to detect, contain, eradicate, and recover from adversarial attacks while maintaining operational continuity and regulatory compliance.

Why Adversarial ML Requires a Specialized IR Approach

Adversarial ML attacks differ from classic cyber incidents in several fundamental ways:

- Invisible Attacks: Perturbations or malicious inputs often appear normal to humans and evade signature based detection.
- Model Behavior is the Victim: The attacker compromises decisions, not systems—causing silent business impact.
- Attacks Can Persist: Poisoned data or backdoors remain until the model is retrained, making remediation complex.
- High Organizational Stakes: Fraud losses, safety incidents, bias amplification, and compliance violations can be immediate and severe.
- GenAI Interaction Risks: Prompt injection and RAG poisoning allow adversaries to manipulate copilots and autonomous agents without breaching infrastructure.

Therefore, ML IR must incorporate data science, MLOps, security engineering, and business operations into a unified response framework.

The Adversarial ML Incident Lifecycle

A mature ML IR capability must address five key phases:

1. Detection & Alerting

ML-specific anomalies often reveal early signs of compromise. Key detection signals include:

Behavioral Anomalies

- Sudden spikes in false positives or false negatives
- Inconsistent or unstable model predictions
- Distribution shift in predicted classes
- Unusual confidence scores or entropy patterns

Input-Level Indicators

- High similarity between repeated queries (extraction attempts)
- Adversarial noise signatures
- Structured, patterned, or synthetic inputs
- Abnormal volumes of inference requests

Data Pipeline Red Flags

- Outliers in training data distribution
- Unapproved data source additions
- Data drift correlated with external attack campaigns

GenAI-Specific Indicators

- Overly directive prompts (“ignore previous instructions…”)
- Unexpected tool invocation attempts
- Contextually impossible responses from copilots
- Recurrent jailbreak patterns

Detection relies on **continuous monitoring**, specialized detectors (e.g., adversarial filters), model telemetry, endpoint analytics, and drift analysis dashboards.

2. Containment

Once an adversarial incident is suspected, rapid containment is essential to limit further harm.

External Document © 2026 Infosys Limited



External Document © 2026 Infosys Limited

Containment Actions

- **Isolate the affected model:** Route traffic to a shadow model or a last-known-good version.
- **Freeze the pipeline:** Prevent new training runs to avoid amplifying the compromise.
- **Disable vulnerable endpoints:** Temporarily restrict high-risk APIs or block suspicious IPs.
- **Restrict external input sources:** Particularly important in RAG-based GenAI flows.
- **Disable automated agent actions:** Prevent copilots or AI agents from performing sensitive tasks.

Containment must balance safety with business continuity and be governed by preapproved playbooks.

3. Eradication

This phase removes root causes and adversarial artifacts.

Model-Level Eradication

- Identify and remove poisoned samples.
- Detect and neutralize backdoors.
- Analyze model activation patterns and gradient sensitivities.
- For GenAI: reset system prompts, clear context caches, sanitize retrieval stores.

Pipeline & Data Clean-Up

- Validate dataset integrity (hash comparisons, lineage tracing)
- Rebuild feature sets from verified sources.
- Review transformations and notebook versions for tampering.
- Restore validated model registry entries.

Infrastructure & Access Remediation

- Rotate API keys and secrets.
- Patch compromised libraries or dependencies.
- Revalidate container images and deployment manifests.

This phase requires tight collaboration across ML engineers, data scientists, cyber teams, and compliance.

4. Recovery

After eradication, the goal is to restore safe operations with confidence.

Recovery Actions

- **Retrain models** using clean datasets.
- **Recalibrate** performance thresholds.
- Conduct **robustness testing** (stress tests, adversarial evaluations)
- Perform **shadow deployment**, comparing outputs with baselines.
- **Gradually reintroduce traffic** with automated rollback triggers
- Re-enable agent capabilities only after guardrail verification.

Recovery must demonstrate that the model is safe, accurate, and compliant before returning to full production.

5. Lessons Learned & Governance Updates

Post-incident learning enhances long-term resilience.

Key Areas to Review

- Root cause of the attack
- Gaps in data governance, access control, or monitoring
- Response time and coordination efficiency
- Quality of telemetry and detection signals
- Required enhancements to policies, pipelines, or model documentation.

Outputs should feed into:

- AI/ML Governance Board
- Risk committees
- Compliance and model audit cycles
- MLOps improvement roadmaps

This phase reinforces a culture of continuous improvement and reduces recurrence probability.

Incident Response Roles & Responsibilities

Adversarial ML incidents require cross-functional coordination:

CISO / Security Operations

- Lead incident classification and escalation.
- Manage containment and risk communication.

ML Engineering

- Examine pipeline and artifact integrity.
- Lead model rollback and redeployment.

Data Science

- Analyze model behavior shifts.
- Support adversarial detection and retraining.

External Document © 2026 Infosys Limited

Product & Business Owners

- Assess customer impact.
- Prioritize business-continuity decisions.

Legal, Compliance & Privacy

- Evaluate regulatory exposure.
- Oversee reporting requirements.

Clear RACI definitions ensure rapid, coordinated execution.

Adversarial ML IR Playbook Templates

A mature IR program should include playbooks for:

1. Evasion Attack Playbook

- Detect prediction anomalies.
- Block suspicious traffic.
- Deploy adversarial detectors.
- Retrain with adversarial hardening.

2. Data Poisoning Playbook

- Trace data lineage.
- Identify and remove corrupted samples.
- Reset training pipelines.
- Strengthening ingestion validation

3. Model Theft / Extraction Playbook

- Detect high frequency queries.
- Enforce rate limits and ABAC.
- Switch to reduced-output mode (no confidence scores)
- Rotate tokens and block abusive clients.

4. GenAI Prompt/Jailbreak Playbook

- Activate prompt shield.
- Disable external tool access.
- Sanitize RAG stores.
- Re-evaluate system prompt safety.

Metrics and KPIs for ML Incident Response

Executives require visibility into the maturity of ML IR. Important metrics include:

- **MTTD:** Mean Time to Detect adversarial activity.
- **MTTC:** Mean Time to Contain affected models.
- **Adversarial Success Rate:** Percentage of adversarial samples bypassing controls.
- **Extraction Attempt Frequency:** Unusual query patterns
- **Drift and Anomaly Rates**
- **Rollback Frequency:** How often rollback mechanisms are used.

These KPIs support performance tracking and board-level reporting.

The Strategic Value of ML-Aware IR

Organizations that build specialized IR capabilities for ML gain:

- **Reduced operational losses** (fraud, outages, misclassifications)
- **Regulatory resilience** for AI governance frameworks
- **Higher customer trust** in AI-driven services
- **Stronger security posture** against emerging ML-specific threats
- **Faster time-to-recovery** when incidents occur.

In a world where attackers increasingly target AI systems, ML-specific IR is no longer optional—it is **a critical pillar of enterprise resilience.**

Appendix A. Glossary

- Adversarial Example — crafted input to trigger misclassification.
- Differential Privacy — adds noise to protect individuals in data.
- Model Card — documentation of purpose, data, metrics, risks.
- Randomized Smoothing — robustness certification technique.

Appendix B. Standards & Frameworks Mapping

- NIST AI RMF — govern, map, measure, manage across lifecycle.
- ISO/IEC 42001 — AI Management System integrated with org controls.
- MITRE ATLAS — adversarial ML tactics/techniques for threat modeling.

External Document © 2026 Infosys Limited



External Document © 2026 Infosys Limited

References

Adversarial Machine Learning & Threat Taxonomies

1. **NIST AI 1002 E2025 – Adversarial Machine Learning: Taxonomy & Terminology**
   National Institute of Standards and Technology (NIST), 2025.
   Provides the most comprehensive, formal taxonomy of AML attacks and mitigations.
   [csrc.nist.gov]

2. **NISTIR 8269 – Taxonomy and Terminology of Adversarial Machine Learning**
   Foundational terminology widely used in academic and industry threat modeling.
   (Referenced through OWASP AI Exchange)
   [owaspai.org]

3. **MITRE ATLAS Framework (Adversarial Threat Landscape for AI Systems)**
   Comprehensive matrix mapping adversary tactics and techniques against ML systems.
   [atlas.mitre.org]

AI Security Standards, Governance, and Risk Frameworks

4. **NIST AI Risk Management Framework (AI RMF)**
   U.S. NIST's lifecycle-based framework (Map–Measure–Manage–Govern) for AI risk management.(Summaries from SentinelOne and Red Hat confirm coverage)
   [sentinelone.com], [redhat.com]

5. **ISO/IEC 42001:2023 – AI Management System (AIMS)**
   Global AI governance standard covering lifecycle risk management and organizational controls.
   [aws.amazon.com]

6. **ISO/IEC 22989:2022 – AI Concepts and Terminology**
   Defines AI system lifecycle stages referenced by ISO/IEC 42001.
   (Discussed in AWS Security Blog)
   [aws.amazon.com]

7. **Google Secure AI Framework (SAIF)**
   Establishes secure AI supply chain principles (covered in SentinelOne's overview).
   [sentinelone.com]

GenAI, LLM, and Agent Security

8. **OWASP LLM Top10 (2024–2025)**
   Global standard for risks related to Large Language Models. Listed in OWASP AI Exchange reference library.
   [owaspai.org]

9. **OWASP GenAI Security Project & Agentic AI Top10**
   Focus on GenAI prompt injection, RAG poisoning, agent misuse, and safety bypass vectors.
   [owaspai.org]

10. **ENISA – AI Threat Landscape & ML Threats & Countermeasures**
    European Union Agency for Cybersecurity's authoritative guidelines on AI risks.
    [owaspai.org]

AI/ML Supply Chain Security

11. **Sightline – AI/ML Supply Chain Vulnerability Database**
    Catalog of real-world AI supply chain risks, dependencies, exposed datasets, and model-based vulnerabilities.
    (Referenced via OWASP AI Exchange)
    [owaspai.org]

12. **OECD AI Incidents Monitor / AI Incident Databases**
    Used globally to track real-world failures, misuses, and vulnerabilities in AI systems.
    [owaspai.org]

External Document © 2026 Infosys Limited

About the Author



Rajesh Kumar Mohapatra is a Cyber Security leader with over 14 years of experience in security architecture, cloud security, infrastructure security, governance, risk management, and operational resilience. He specializes in securing hybrid enterprise environments across Azure Cloud Security and on-premises platforms, with expertise in Firewalls, Proxies, Cisco ISE, EDR/DR, Email Security, Identity Security, and Data Security. With a growing focus on AI-driven security and Responsible AI, Rajesh helps organizations address emerging risks associated with AI adoption through secure design, governance, and compliance frameworks. Currently serving as Principal Consultant - Infrastructure Management and Technology Manager (Cyber Security), he partners with business and technology leaders to drive secure digital transformation, strengthen cyber resilience, and align security strategies with organizational goals.

For more information, contact askus@infosys.com

Infosys
Navigate your next

© 2026 Infosys Limited, Bengaluru, India. All Rights Reserved. Infosys believes the information in this document is accurate as of its publication date; such information is subject to change without notice. Infosys acknowledges the proprietary rights of other companies to the trademarks, product names and such other intellectual property rights mentioned in this document. Except as expressly permitted, neither this documentation nor any part of it may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, printing, photocopying, recording or otherwise, without the prior permission of Infosys Limited and/ or any named intellectual property rights holders under this document.